


**Shut-off valve**


- ▶ 3/2 N.C. poppet valve for opening and exhausting the circuit
- ▶ Allows to pneumatically supply the part of the system downstream of the valve
- ▶ Manual adjusting lockable handle (in shut-off position) with a maximum of three pad-locks
- ▶ Atex certification (II 2GD o II 3GD) on request


**AIR TREATMENT**
**Technical characteristics**

| Size   | Size 1  | Size 2  | Size 3                                      | Size 4                                      |
|--|---|---|---|---|
| Body and connections type                    | Zinc alloy body,<br>Zinc alloy integrated connections<br>Technopolymer body,<br>metal connections | Aluminium body,<br>integrated aluminium connections |   |   |
| Operated type                                | Manual  |   |   |   |
| IN / OUT connections                         | G1/4"   | G3/8"   | G1/2"                                       | G1"   |
| Discharge connections                        | G1/8"   | G1/4"   | G3/8"                                       | G1/4"                                       |
| Assembly configuration                       | Stand alone<br>Panel mounted with M4 screws   | Stand alone<br>Panel mounted with M5 screws         | Stand alone<br>Panel mounted with M6 screws | Stand alone<br>Panel mounted with M8 screws |
| Assembly position                            | Indifferent   |   |   |   |
| Max. fittings torque<br>IN / OUT connections | G1/4" metal: 20   | G3/8" metal: 25                                     | G1/2" metal: 30                             | G1" metal: 35                               |

**Operational characteristics**

| Size   | Size 1     | Size 2 | Size 3 | Size 4 |
|--|------------|--------|--------|--------|
| Maximum working pressure (bar)                           | 13         |        |        | 10     |
| Minimum working pressure (bar)                           | 0,5        |        |        |        |
| Nominal flow rate at 6 bar<br>with $\Delta p=1$ (NI/min) | 1000       | 2100   | 2500   | 8000   |
| Working temperature (°C)                                 | -5 ... +50 |        |        |        |

**Weights**

| Size                           | Size 1 | Size 2 | Size 3 | Size 4 |
|--------------------------------|--------|--------|--------|--------|
| Zinc alloy body version (g)    | 280    | /      | /      | /      |
| Technopolymer body version (g) | 155    | /      | /      | /      |
| Aluminium body version (g)     | /      | 380    | 550    | 1600   |

Order codes

17 330 . A

| Size, body and connections |   |
|----------------------------|---|
| 030                        | Zinc alloy body, connections G1/4" (only for size 1)    |
| 130                        | Technopolymer body, connections G1/4" (only for size 1) |
| 230                        | Aluminium body, connections G3/8" (only for size 2)     |
| 330                        | Aluminium body, connections G1/2" (only for size 3)     |
| 430                        | Aluminium body, connections G1" (only for size 4)       |

| Type |                     |
|------|---------------------|
| A    | Not lockable handle |
| B    | Lockable handle     |

Example: 17330.A

Shut-off valve Size 3, Aluminium body, G1/2" connections, with not lockable handle

Dimensions

