



## Manual valves

### Series 500



The manual valves, 504-505 series, are produced in Italy according to the reference ISO norms as warranty of high quality level.

### Technical sheet


CONNECTING TUBES		Normally not applied directly to pipes, however defined according to the applications
TEMPERATURE AND PRESSURE	Working temperature	from -20° to +70° °C
	Max. working pressure	10 bar
THREAD TYPE		BSP parallel UNI-ISO 228
MATERIALS	Series 505 body	Brass UNI EN 12165 CW617N
	Series 504 body Series 504-505 slider	Anodized aluminum
	Seals gasket	NBR 70 DWGV-EN549 UL157

ART. 504

## Hand slide valve



COD.	A	B	C	掣	盒	kg
50418	G1/8	25	40	14	10	42,00
50414	G1/4	30	46	17	10	74,00
50438	G3/8	35	52	21	10	122,00
50412	G1/2	40	62	26	10	170,00



ART. 505

## Brass hand slide valve



COD.	A	B	C	掣	盒	kg
505M5	M5	14	30,5	10	10	11,80
50518	G1/8	25	48	14	10	50,50
50514	G1/4	30	58	19	10	95,50
50538	G3/8	35	70	22	10	154,00
50512	G1/2	40	75	27	10	210,00
50534	G3/4	50	83	32	10	187,00

